



www.kspowertools.com

kspowertools

à'„à,®à, ”à,£à,-à,¥à,´à,,POWERRAM _



HYDRAULIC POWERRAMÂ HYDRAULICÂ PULLERS



CYLINDERS à,•à,£à,°à,šà,-à,•à'„à,®à, ”à,£à,-à,¥à,´à,,
à,£à,1à,•à,šà,‡ NSHS

[Call for Pricing](#)

Powerram Cylinders Hollow à,£à,1à,•à,šà,‡ [\[Product Details...\]](#)



PULLER

à,ªà,²à,jà,à,²à,²à,¹à,²à,²à,¹à¹€à,¥à¹^à¹,,à,®à,²à,£à,-à,¥à,´à,,
POWERRAM
[Call for Pricing](#)

[\[Product Details...\]](#)



à,•à,£à,°à,šà,-à,•à¹,,à,®à,²à,£à,-à,¥à,´à,•NSSS à,ªà¹,à,à,£à,•
25-362à,jà,j.
[Call for Pricing](#)

[\[Product Details...\]](#)



à,•à,£à,°à,šà,-à,•à',,à,®à,"à,£à,-à,¥à,´à,•à,—à,£à,†à¹€à,•à,µà¹%à,¢
NSCS à,ªà¹,à,•à,•38-62à,ìà,ì.

[Call for Pricing](#)

[\[Product Details...\]](#)



à,•à,£à,°à,šà,-à,•à',à,®à,"à,£à,-à,¥à,´à,,
à,£à,¹à,—à,°à,¥à,,12à,•à,±à,™

[Call for Pricing](#)

กระบอก 12ตัน แบบรูป กลวง	
สโตก	42 มม.
สูงก่อนยก	120 มม.
ยกสูงรวม	162 มม.
เส้นผ่าศูนย์กลางรู	19.5 มม.

[\[Product Details...\]](#)



à,•à,£à,°à,šà,-à,•à',à,®à,"à,£à,-à,¥à,´à,, à¹à,šà,šà,£à,¹à,•à,šà,‡

[Call for Pricing](#)

ขนาด 20 ตัน	
สูงก่อนใช้งาน	306 มม.
ยกสูงสุด	463 มม.
สโตก	155 มม.
ขนาดรู	27 มม.
ความโตกระบอก	98.5 มม.

[\[Product Details...\]](#)

POWERRAM // CYLINDERS



MODEL: NSLS-SERIES

Capacity: 5-150Ton
Stroke: 6-16 mm
Max. working pressure:
10,000 psi / 700 bar



www.kspowertools.com

NSLS

[Call for Pricing](#)

[\[Product Details...\]](#)



à Šà, à ”à •à £à °à šà -à •à 1,,à ©à ”à £à -à ¥à ´à ,,12à •à ±à ™
[Call for Pricing](#)

[\[Product Details...\]](#)



à, à, ±à'Šà, jà', à, ©à, "à, £à, -à, ¥à, ^à, ,,à'fà, Šà'‰à, ¥à, jAP1600
[Call for Pricing](#)

[\[Product Details...\]](#)



à, Ÿà,, à, •à, ›à, ±à'Šà, jà', à, @à, "à, £à, -à, ¥à, 'à, ,, à'fà, Šà'‰à, ¥à,
AP-921

[Call for Pricing](#)

à, Ÿà,, à, •à, ›à, ±à'Šà, jà', à, @à, "à, £à, -à, ¥à, 'à, ,, -à, ¥à, j [\[Product Details...\]](#)



à, ºà, ²à, jà, ,à, ²à, "à, 1à, "à, ¥à, 1à, •à, ›à, -à, ™ à', à, @à, "à, £à, -à, ¥à, 'à, ,,
[Call for Pricing](#)

[\[Product Details...\]](#)

POWERRAM // MECHANICAL EASY PULLERS

เบอร์โทร. อุปกรณ์เครื่องมือช่าง
02-0411710
081-9217280
080-0892106
Line : kspowertools / 081-9217280



www.Kspowertools.com

à¹€à, «à, ¥à¹†à, •à, ”à, 1à, ”3à, ,à, ²à¹•à, šà, šà¹€à, •à, ¥à, µà, çà, §à, «à, ja, ,à, ™
[Call for Pricing](#)

[\[Product Details...\]](#)



à¹•à, ®à, ™à, ”à, ,à, ±à¹Šà, ja¹, ,à, ®à, ”à, £à, -à, ¥à, ´à, ,, HA-700
POWERRAM
[Call for Pricing](#)

[\[Product Details...\]](#)



à¹•à, ®à, ™à, ”à¹€à, ,à, ±à¹Šà, ja¹, ,à, ®à, ”à, £à, -à, ¥à, ´à, ,, PA-600-700
[Call for Pricing](#)

[\[Product Details...\]](#)

POWERRAM // SPECIAL HAND PUMPS **KSPowERTOOLS**
THE QUALITY MANUFACTURING
FOR PROFESSIONALS WHO DO NOT SETTLE

P350A



FEATURES:

- Powerram's hand pumps are always featured with their rugged construction and low handle efforts.
- Aluminum alloy construction and hand size release levers with anti-leaking mechanism are truly suitable to industrial requirements and your daily needs.
- Special design with aluminum alloy construction as much light weight is ideal for easy portability and maneuvering.
- Builder of reservoir design allows the hand pumps to be operated in all directions.
- Unique design of Triangle socket end create much easy pumping efforts.
- The patent pending design of P350A consolidating pump and manifold valve as one piece that makes much convenient job on operating two single-acting cylinders at the same time, but eliminating the extra needed adapters and accessories.

www.kspowertools.com

à¹•à¸¸™à¸¸”à¹CEà¸¸,à¸¸±à¹Šà¸¸,à¸¸à¸¸”à¸¸£à¸¸-à¸¸¥à¸¸`à¸¸,,
Powerram P350-A
[Call for Pricing](#)

[\[Product Details...\]](#)

POWERRAM // HAND PUMPS **KSPowERTOOLS**
THE QUALITY MANUFACTURING
FOR PROFESSIONALS WHO DO NOT SETTLE

Max. Working Pressure 700 bar / 10,000 psi
Large 3/8" pressure port for maximum flow
Low Handle effort for easy operation • Two speed models



www.kspowertools.com / www.kcm2539.com

HE2421

à¹•à, @à, ™à, ”à¹CEà, ,à, ±à¹Šà, ,à¹, ,à, @à, ”à, £à, -à, ¥à, ´à, ,,2à, —à, ?à, †

HE-2421

[Call for Pricing](#)

[\[Product Details...\]](#)

Max. Working Pressure 700 bar / 10,000 psi
Large 3/8" pressure port for maximum flow
Low Handle effort for easy operation
Single & Two speed models



