




[www.kspowertools.com](http://www.kspowertools.com)

*kspowertools*

à¹,à\_®à\_”à\_£à\_-à\_¥à\_´à\_•à\_ªà¹CE KUDOS \_  




**HYDRAULIC SPREADERS KUDOS**  
[Call for Pricing](#)

[\[Product Details...\]](#)



Model No. SH-70A

Specifications:  
 Throat Depth: 70 mm  
 Max. Pressure: 700 bar  
 Oil Required: 82 cc  
 Punching Capacity:  
 Max. Thickness : 10 mm  
 Max. Diameter : 20.5 mm  
 20.5 mm diameter hole with 10 mm  
 thick mild steel.  
 For angle iron, plates, beams and bus bars.  
 Round Punching Dies for mild steel  
 (10.5, 13.5, 17.5, 20.5 mm)  
 Hand Pin, 4 mm T-type Wrench  
 Square Punching Dies :  
 1/2", 3/8", 5/16", 7/16"  
 Height: 360 mm

**PUNCHING à¹,à\_®à\_”à\_£à\_-à\_¥à\_´à\_„**  
 à\_žà\_±à¹%à\_™à¹€à\_à²à\_°à\_£à¹  
[Call for Pricing](#)

[\[Product Details...\]](#)

- 
- 
- 
- 
- 

«« Start  
« Prev  
1  
Next »  
End »»

Results 1 - 2 of 2